

Russ Andrews® SUPERFUSE™



Do not attempt to replace the mains fuse on a Russ Andrews **SuperKord**. The fuses in these mains cables are factory-replaceable only and cannot be replaced by the user. Please contact us if you need any more information.

Features

- Russ Andrews SuperFuse features our unique Super Burn-in treatment
- End caps are hand-polished and treated with DeoxIT® contact enhancer
- Proprietary plating and fuse wire
- Ceramic body
- Supplied with DeoxIT® Gold wipe
- Manufactured to BS 1362
- Length: 25.4mm Diameter: 6.3mm

WARNING: Only replace a fuse with a SuperFuse of the same rating that is correct for the cable it is fitted to.

Contact us:

Mon-Fri 9am - 5.00pm 01539 797300

From outside UK: 0044 1539 797300

Email: info@russandrews.com

Web: www.russandrews.com

Russ Andrews®

Russ Andrews Accessories Ltd., 2B Moreland Court
Westmorland Business Park, Shap Road, Kendal,
Cumbria, LA9 6NS, UK

Instructions for use

Please note that you should replace an existing fuse with a SuperFuse of the same rating: ie an existing 13A fuse should be replaced with a 13A SuperFuse. Do not be tempted to fit a higher-rated SuperFuse than the one in your existing cable; it may be a safety risk. Conversely fitting a lower-rated SuperFuse than the one fitted to your cable may compromise its performance.

Preparation

Before fitting your new SuperFuse™ treat the end caps with the enclosed DeoxIT® Gold wipe for optimum performance. *Tip! There is enough DeoxIT® Gold in the wipe to treat your plug pins too.*

1. If fitting to a Russ Andrews mains cable, remove the 'Warranty - Void if Removed*' or 'Fitted with Russ Andrews fuse' sticker or poke through it with a screwdriver to gain access to the screw.
** Note: you will not void your warranty if you remove the sticker simply to replace the fuse.*
2. Using a correct sized screwdriver, undo the screw/s to take the top off the plug.
3. Remove the existing fuse and replace it with the SuperFuse™.

4. Put the lid back on the plug and screw tightly back together.
5. Finally, affix the 'Fitted with SuperFuse™' label over the screw or on the lid of your plug to identify that it has been upgraded.

The SuperFuse™ should be fitted as follows:



We accept no responsibility for any damage caused to any part of your plug, cable or equipment through improper use of this product